GLOBALFUND TRADING XCHANGE
Specification of Products
KRS: 0000788803, NIP: 9691637502, REGON: 383502354
Przemysłowa 1C, 59-300 Lubin, Poland
Phone: +48 768415087, Email: info@globalfundtrading.net

ALL ASIA CEMENT
EXPORT QUALITY

Portland Cement 52.5

PRODUCT SPECIFICATION

52.5

Portland cement of strength class 52.5 with high early strength, for houses and buildings, bridges, roads, airports and runways, and precast and pre-stressed concrete. It is sold under All Asia Cement, the brand of All Asia Steel & Cement Corp., a GFTx company, produced at the plant of Yixing Dongyi Building Materials Co., Ltd. in Yixing, Jiangsu, China, and supplied by GFTx in 40 kg bags across Asia and beyond, for example in Singapore and the Philippines.

PRODUCT

Type	Portland cement
Strength class	52.5
Early strength	High, as stated on the bag
Brand	All Asia Cement · Export Quality

PACKING & MARKING

Net weight	40 kg per bag
Bag size	50 × 57 × 11 cm
Marking	Batch identification number and manufacturing date on each bag

MIXING GUIDE (PRINTED ON THE BAG)

Application	Cement	Sand	Stone	Water
Concrete	1 part	2 parts	3 parts	As needed
Patching & plastering	1 part	7 parts	—	As needed
Wall coating	1 part	—	—	As needed
Ceramic patching	1 part	3 parts	—	As needed

SUPPLY

Brand owner	All Asia Steel & Cement Corp., a GFTx company (registered with the SEC, Philippines)
Manufacturer	Yixing Dongyi Building Materials Co., Ltd., Meixi Village, Xushe Town, Yixing City, Jiangsu Province, China
Markets	Across Asia and beyond, e.g. Singapore and the Philippines
Documents	Test report and certificate of analysis on request

APPLICATIONS

Houses & buildings · Bridges · Roads, airports & runways · Precast & pre-stressed concrete

PRECAUTIONS (PRINTED ON THE BAG)

- ✓ **Skin and eyes** — contact with cement may cause irritation or skin damage
- ✓ **Protective equipment** — wear suitable protective clothing and equipment when working with cement
- ✓ **Eye contact** — rinse immediately with water and ask for medical advice if necessary
- ✓ **Children** — keep out of reach of children

From the All Asia Cement bag (Portland Cement 52.5, 40 kg). Strength class 52.5 means a 28-day compressive strength of at least 52.5 MPa. The bag does not name the cement standard; chemical and physical test values are given in the manufacturer's test report, available on request. Prices and availability are quoted on request: info@globalfundtrading.net.

© 2026 GFTx. All rights reserved.